



# C<sup>2</sup> PROTECTOR™

## FREQUENTLY ASKED QUESTIONS

### **WHAT IS C<sup>2</sup> PROTECTOR?**

C<sup>2</sup> Protector is a VOC-compliant, mild solvent-based, penetrating water, oil and stain repellent that can be applied to every kind of finished concrete flooring. Treated surfaces retain their natural appearance, texture and breathability, and feature improved stain resistance, which simplifies the maintenance cleaning process.

### **IS C<sup>2</sup> PROTECTOR VOC-COMPLIANT?**

Yes, C<sup>2</sup> Protector is compliant with the US Environmental Protection Agency's AIM OC regulations. C<sup>2</sup> Protector ships as a "non-hazardous" item both by sea and air, domestically and internationally. Contact us at [sales@cretecolors.com](mailto:sales@cretecolors.com) for compliance questions with individual country regulations.

### **BEING SOLVENT-BASED, DOES IT HAVE AN ODOR?**

C<sup>2</sup> Protector has very little, if any, odor, and is suitable for use in occupied spaces.

### **WHERE IS C<sup>2</sup> PROTECTOR BEST SUITED FOR USE?**

C<sup>2</sup> Protector is ideal for use in areas where spills and stains occur and where no additional surface sheen and enhancement is desired. Additionally, it is recommended for areas of high traffic or wheeled traffic where surface film-forming sealers may prematurely wear off.

### **ARE THERE PLACES C<sup>2</sup> PROTECTOR IS NOT RECOMMENDED FOR USE?**

C<sup>2</sup> Protector is not recommended for areas exposed to long-standing periods of water ponding or below-grade applications. This product will not provide UV protection to concrete floors colored with C<sup>2</sup> Tint or C<sup>2</sup> Color Hard. C<sup>2</sup> Seal or C<sup>2</sup> Ultra Seal are more appropriate.

### **CAN C<sup>2</sup> PROTECTOR BE BURNISHED?**

Once dry, C<sup>2</sup> Protector may be burnished using a high-speed burnisher fitted with a C<sup>2</sup> Heat burnishing pad #1500, or #3000 grit diamond impregnated pad suitable for use on high-gloss finishes. In addition to smoothing and polishing the treated surface, high-speed burnishing can help to remove any surface haze from possible over-application. Best results are obtained when C<sup>2</sup> Protector is allowed to dry for at least 4 hours prior to burnishing.

### **CAN YOU APPLY C<sup>2</sup> PROTECTOR OVER C<sup>2</sup> SEAL OR C<sup>2</sup> ULTRA SEAL?**

Yes, C<sup>2</sup> Protector may be applied to surfaces previously treated with C<sup>2</sup> Seal or C<sup>2</sup> Ultra Seal. Please refer to the product data sheets for appropriate coverage rates.