



# C<sup>2</sup> Heat™

## High Performance Burnishing Pads

---



### DESCRIPTION AND USE

The C<sup>2</sup> Seal™ microfilm is melded into the concrete floor through 33°C\* of heat from friction, producing gloss and durability beyond compare. The C<sup>2</sup> Heat™ High-Performance Burnishing Pad gives you 33°C\* faster and longer than ordinary pads.

### BENEFITS

- Embedded membrane stops heat from rising and bounces it back into the floor
- Double-sided for double service life
- All-natural fibers glued together with non-transferring resin
- No resin trails will be left on a concrete surface
- Designed to burnish C<sup>2</sup> Seal™ but can be also used for polishing and maintenance
- Available for immediate delivery in the following sizes  
27 inch, 24 inch, 20 inch and 7.5 inch
- Available by special order in additional 17 specialty sizes  
From 9 inch to 28 inch
- Cost efficient through increased usage life
- Available in cases – 5 pads per case

### CUSTOMER SERVICE

For technical assistance and product information visit our web site at [www.cretecolors.com](http://www.cretecolors.com) or email at [support@cretecolors.com](mailto:support@cretecolors.com)

\* 33°C is equivalent to 91.5°F



# C<sup>2</sup> Heat™

## High Performance Burnishing Pads

---

### AVAILABLE IMMEDIATELY

7.5 inch	(213 mm)
20 inch	(508 mm)
24 inch	(610 mm)
27 inch	(686 mm)

### AVAILABLE BY SPECIAL ORDER

9 inch	(229 mm)
10 inch	(254 mm)
11 inch	(280 mm)
12 inch	(305 mm)
13 inch	(330 mm)
14 inch	(356 mm)
15 inch	(381 mm)
16 inch	(407 mm)
17 inch	(432 mm)
18 inch	(457 mm)
19 inch	(483 mm)
21 inch	(534 mm)
22 inch	(559 mm)
23 inch	(584 mm)
25 inch	(635 mm)
26 inch	(661 mm)
28 inch	(711 mm)

